

PT475 Standard and Optional Features List

Standard Features

1. Manufactured in an NPCA Certified Plant to insure the highest industry standards are maintained.
2. Exterior Ashler Stone appearance (bottom), Random Grooved Barnwood appearance (top). Painted to owner's choice from standard chart of colors.
3. Four skylights cast into the roof.
4. Two 12" diameter black HDPE vent pipes extending approximately 3' above the roof line.
5. Two aluminum 24" x 24" clear through access/clean out hatches with padlock staple. Padlocks not included.
6. Four 8" x 30" vinyl bug screen windows.
7. Four 16" x 8" Ledbetter floor vents.
8. Two 3-0 x 6-8 16ga steel frames and insulated 18ga flush doors:
 - a. Ball bearing hinges
 - b. Door closure
 - c. Grade 1 keyed/push button lever handle lockset (can be keyed to owner's key)
 - d. Safety chain
 - e. Adjustable aluminum/vinyl door sweep
9. Three steel stall doors.
10. One stainless steel floor mounted urinal.
11. Three white cross stitched polyethylene stools and seats.
12. Two 42" stainless steel grab bars, and two 36" stainless steel grab bars.
13. Three stainless steel 3 roll toilet paper dispensers, padlocks included.
14. Two floor drains.
15. Interior painted with a high quality acrylic satin, off white.
16. Precast concrete vault with 4" thick sidewalls and 6" thick floor, interior sealed with Conseal CS-55.

Optional Features

1. Owner's choice of available options for exterior appearance.
2. Colored concrete.
3. Epoxy paint interior and/or exterior.
4. Anti-graffiti coating interior and/or exterior.
5. Galvanized or fiberglass door.
6. Plastic stall doors.
7. Deadbolt, push/pull plate, threshold, bulb seal, spring loaded hinges.
8. Continuous grab bar.
9. Heavy duty 3 roll toilet paper dispenser.
10. Stainless steel stool.
11. Electrical options for photovoltaic and underground electric.
12. Precast concrete stoop.