

PT175 Standard and Optional Features List

Standard Features

1. Manufactured in an NPCA Certified Plant to insure the highest industry standards are maintained.
2. Exterior Ashler Stone appearance (bottom), Random Grooved Barnwood appearance (top). Painted to owner's choice from standard chart of colors.
3. One skylight cast into the roof.
4. One 12" diameter black HDPE vent pipe extending approximately 3' above the roof line.
5. One aluminum 24" x 24" clear through access/clean out hatch with padlock staple. Padlock not included.
6. One 3-0 x 6-8 16ga steel frame and insulated 18ga flush door:
 - a. Ball bearing hinges
 - b. Door closure
 - c. Grade 1 keyed/push button lever handle lockset (can be keyed to owner's key)
 - d. Safety chain
 - e. Adjustable aluminum/vinyl door sweep
7. One stainless steel floor mounted urinal.
8. One white cross stitched polyethylene stool and seat.
9. One 42" stainless steel grab bar, and one 36" stainless steel grab bar.
10. One stainless steel 3 roll toilet paper dispenser, padlock included.
11. One floor drain.
12. Interior painted with a high quality acrylic satin, off white.
13. Precast concrete vault with 4" thick sidewalls and 6" thick floor, interior sealed with Conseal CS-55.

Optional Features

1. Owner's choice of available options for exterior appearance.
2. Colored concrete.
3. Epoxy paint interior and/or exterior.
4. Anti-graffiti coating interior and/or exterior.
5. Galvanized or fiberglass door.
6. Deadbolt, push/pull plate, threshold, bulb seal, spring loaded hinges.
7. Continuous grab bar.
8. Heavy duty 3 roll toilet paper dispenser.
9. Stainless steel stool.
10. Electrical options for photovoltaic and underground electric.
11. Precast concrete stoop.